

Bridgeport Prefabricated Fireproof Columns (Type OH)						
WIDE FLANGE SHAPES - UL RATED						
WF size	X106 - 2 Hour		X104 - 3 Hour		X101 - 4 Hour	
	Shell Size	Wt. †	Shell Size	Wt. †	Shell Size	Wt. †
4x13	8 5/8	29	8 5/8	29	8 5/8	29
W5x16, 19	8 5/8	29	10 3/4	45	10 3/4	45
W6x15, 20	10 3/4	45	10 3/4	45	12 3/4	63
W6x25	10 3/4	44	12 3/4	63	12 3/4	63
W8x18, 21	12 3/4	63	12 3/4	63	12 3/4	63
W8x24, 28	12 3/4	63	12 3/4	63	14	78
W8x31	14	77	14	77	14	77
W8x35, 40, 48	14	76	14	76	16	95
W8x58, 67	14	75	16	94	16	94
W10x22, 26, 30	14	77	14	77	16	96
W10x33, 39, 45	16	95	16	95	16	95
W10x49, 54	16	94	18	115	18	115
W10x60, 68, 77	18	112	18	112	18	112
W19x88, 100	18	111	18	111	18	111
W10x112	18	110	18	110	20	132
W12x26, 30	16	96	16	96	18	117
W12x35	16	96	18	116	18	116
W12x40, 45, 50	18	116	18	116	18	116
W12x53, 58	18	115	18	115	20	138
W12x65, 72, 79	20	136	20	136	20	136
W12x87, 96, 106	20	134	20	134	22	158
W12x120, 136	20	132	22	156	22	156
W12x152, 170	22	153	22	153	22	153
W12x190	22	150	22	150	22	150

† Weight shown in pounds per foot for shell and fireproofing only.

All shell sizes are shown in inches.

Information available upon request for sizes other than shown.

Refer to latest edition of A.I.S.C. steel construction manual for allowable safe loads.

**Black Rock Column, Inc.**

Downloaded from <http://www.blackrockcolumn.com>